

HETRON® 922 PAS

C260011

HETRON® 922 PAW

C260012

HETRON 922PAS and HETRON 922PAW are promoted, thixotropic and wax free Epoxy Vinyl Ester resins formulated to provide excellent performance in a wide range of composite applications demanding good chemical resistance.

Selection of the correct resin for a given chemical environment is very important and reference should be made to the current version of the Ashland publication - "**HETRON® and AROPOL™ Resin Selection Guide**", in conjunction with Nuplex Composites Technical Service staff.

HETRON 922PAS and HETRON 922PAW are now part of the comprehensive range of corrosion resistant Vinyl Esters made locally by Nuplex Composites under licence to Ashland Chemical Co.

FEATURES & ADVANTAGES

- Excellent in corrosion and chemical and resistance
- Excellent impact strength
- High tensile elongation

CORROSION RESISTANCE:

HETRON 922PAS and HETRON 922PAW show good chemical resistance to a wide range of corrosive environments. Due to the thixotropic content, it is not suitable for applications where strong oxidising agents are present egs. Sodium Hypochlorite, Hydrofluoric Acid, etc. For optimum chemical resistance the non-thixotropic resin, **HETRON® 922** should be used in the corrosion layer of the laminate. In most cases the structural layer of the corrosion resistant laminate can be completed with **HETRON 922PAS/PAW**.

SUGGESTED USE

Product can be used for Corrosion resistant tanks, pipes, vats, process vessels, pumps, scrubbers, and other equipment. Also suitable for flake-glass or fibreglass reinforced linings, coatings and monolithic toppings on tanks, vats, floors, troughs, and similar applications.

TYPICAL LIQUID RESIN PROPERTIES

PROPERTY	TYPICAL VALUE	PAS	PAW
Geltime (minutes)	@ 25° C, 1.25% Curox®M-100 Catalyst	35-40	25-30
Specific Gravity	@ 25° C	1.05	
Shelf Life	When stored in original closed container in the shade	3 months	
Monomer Content %		48	

* Typical values: Based on materials tested in our laboratories, but varies from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

TYPICAL CURED RESIN CASTING PROPERTIES

PROPERTY	TYPICAL VALUE	TEST DETAILS
Hardness	30	Barcol (GYZ 934-1) EN 59
Specific Gravity	1.12	
Tensile Strength	86 (MPa)	ISO R527
Flexural Strength	141 (MPa)	ISO 178
Flexural Modulus	3.4 (GPa)	ISO 178
Heat Deflection Temperature	100° C	ISO 175 (1.82 MPa)

* Cast resin was prepared as laid down in BS 3532 using 1% MEKP. Cured at room temperature for sixteen hours then post cured for two hours at 80° C followed by two hours at 100° C.

Australia A Division of Nuplex Industries (Aust) Pty Limited
 Sydney T: +61 2 9666 0331 F: +61 2 9666 6661
Vietnam Nuplex Resins (Vietnam) Pty Limited
 Ho Chi Minh T: +84 61 3836 503 F: +84 61 3836 633

New Zealand
 Auckland
Indonesia
 Surabaya

A Division of Nuplex Industries (NZ) Limited
 T: +64 9 583 6500 F: +64 9 525 3709
PT Nuplex Raung Resins
 T: +62 31 842 0391 F: +62 31 847 7426

This information appearing in this Document (Details) concerning the product, which is the subject of the Document (Product) is either based on present technical knowledge and tests done by Nuplex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of Nuplex, no warranty or representation, express or implied is made by Nuplex regarding the suitability for such use, nor does Nuplex accept any liability arising out of the use by you or other products or materials, whether third party or not, that may be referred to in this Document. Nuplex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, Nuplex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against Nuplex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. Nuplex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of Nuplex, which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree:

- The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government.
- The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it.
- Nuplex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use.
- Nuplex's liability for breach of any term, condition, guarantee or warranty (express or implied) and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at Nuplex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.

Technical Data Sheet



GELTIME VARIATION WITH TEMPERATURE AND CATALYST (Guide Only)

HETRON® 922 PAS						
Temperature	% Cadox L50a CATALYST			% Curox® M-100 CATALYST		
° C	2.0	1.5	1.25	2.0	1.5	1.25
15	58	N/R	N/R	54	N/R	N/R
20	46	65	N/R	31	41	49
25	28	40	47	23	30	36
30	20	28	33	16	20	23
35	N/R	17	19	N/R	N/R	15

HETRON® 922 PAW						
Temperature	% Cadox L50a CATALYST			% Curox® M-100 CATALYST		
° C	2.0	1.5	1.25	2.0	1.5	1.25
15	40	N/R	N/R	41	50	57
20	31	38	42	28	31	34
25	21	27	31	19	21	25
30	15	19	21	13	15	16
35	N/R	14	16	N/R	N/R	11

Post curing is recommended for maximum chemical and heat resistance

Note: Geltimes are in minutes

N/R: Not recommended

STORAGE AND HANDLING

To ensure maximum stability and maintain optimum resin handling properties, this product should be stored in closed containers, away from heat sources and sunlight. The product must be stored away from all sources of ignition. Stored resin quantities should be kept to a reasonable minimum and used on a first in/first out stock rotation basis. Prolonged storage, or unfavourable storing conditions, may cause separation, therefore agitation of the resin before use is recommended.

STANDARD PACKAGING

Mild steel drums (open top)

Mild steel pails

Always refer to the MSDS before use.

DV0914

Australia
A Division of Nuplex Industries (Aust) Pty Limited
 Sydney T: +61 2 9666 0331 F: +61 2 9666 6661
 Vietnam **Nuplex Resins (Vietnam) Pty Limited**
 Ho Chi Minh T: +84 61 3836 503 F: +84 61 3836 633

New Zealand
 Auckland
Indonesia
 Surabaya

A Division of Nuplex Industries (NZ) Limited
 T: +64 9 583 6500 F: +64 9 525 3709
PT Nuplex Raung Resins
 T: +62 31 842 0391 F: +62 31 847 7426

This information appearing in this Document (Details) concerning the product, which is the subject of the Document (Product) is either based on present technical knowledge and tests done by Nuplex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of Nuplex, no warranty or representation, express or implied is made by Nuplex regarding the suitability for such use, nor does Nuplex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. Nuplex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, Nuplex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against Nuplex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. Nuplex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of Nuplex, which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree:

- The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government.
- The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it.
- Nuplex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use.
- Nuplex's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at Nuplex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.